

Product data sheet


COMPASS SPOT
03.3321/HIT-CRI/70W/12°
FLOS




IP
20

Range of indoor spotlights for accent and general lighting for three-phase track and wall/ceiling installation. Die-cast aluminium alloy, powder-coated optics compartment, diameter 118 mm, composed of an aluminium dissipating element placed above the lamp support, a black thermoplastic screen support ring and 4 mm tempered glass cover. Integrated auxiliary power units for the lamps inside a die-cast aluminium alloy container with powder-coated finish.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	62%
Luminous efficacy	58 lm/W	Total flux	4093 lm
CCT	4200 K	Total power	70 W
CRI	94		



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	62%
Luminous efficacy	58 lm/W	Total flux	4093 lm
CCT	3000 K	Total power	70 W
CRI	83		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in

Width: 4.72 in

Height: 5.83 in

Adjustability

Free

Electric

System power: 70 W

Protection

IP: 20