



Product data sheet

FLAT BASIC
211344.002.3.19
RZB



Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. Functional parameters of the motion detector (ceiling mounting up to 4.0m or wall mounting up to 2.7m): HF detector 5.8GHz ISM frequency band. Sensitivity/Range: 1-8m in diameter, adjustable from 20-100%. Time control between 10seconds and 30minutes, adjustable. Coverage: 120°. Can be used as master luminaire up to 800W (ohmic load), 500W (fluorescent lamp, LED) / 400A, 200 µs. Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: white Diameter: 370mm Height: 118mm Lamp: A60 Number of lamps: 1 Wattage: 60W Socket: E27 System power: 46W Rated luminous flux: 470lm Luminous efficiency: 10lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP43

Light output 1



1 x Halogen low voltage lamp without reflector			
Nominal lamp power	46 W	Socket	E27
Lamp flux	700 lm	LOR	67%
Luminous efficacy	10 lm/W	ULOR	14%
CCT	3000 K	Total flux	467 lm
CRI	90	Total power	46 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.65 in
Diameter: 14.57 in

Adjustability

Fixed

Design

Material impression: Matt

Electric

System power: 46 W
Ballast: ECG

Protection

IP: 43
IK: 02
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F