## Product data sheet

LSRS8B/LSRSWM8B LED 8" SHALLOW ROUND CYLINDERS LSR8B30D010 EC8B30940 8LBM0WMH

**COOPER LIGHTING** 








Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-6,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

## Light output 1 (integrated)



Lamp type	LED	
Nominal lamp power	27.1 W	
Total flux	2635 lm	
Luminous efficacy	97 lm/W	

 LED
 CCT
 4000 K

 27.1 W
 CRI
 90

 2635 lm
 LOR
 100%

 97 lm/W
 Total power
 27.1 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in Diameter: 8.00 in

Adjustability

Fixed

Electric

System power: 27.1 W

Protection

IP: 47