Product data sheet

WAVE 600 WHITE SENSOR 2330LM 4000K RA>80 ON/OFF 7021981112868

SG ARMATUREN










Wave LED is an energy-efficient IP44 luminaire for use in corridors, archives and storerooms as well as similar areas with low activity. Luminaire body made of aluminium and diffuser made of acrylic (polycarbonate option available). Wave comes part prewired and can be mounted very quickly, making it an ideal choice in new buildings and when replacing older luminaires. Light distribution Direct Light technic LED 18W 4000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming On/Off Protection Class I IP44 IK06 Materials and finish Housing: Steel, Aluminium Colour: White (RAL 9003) Optics: PMMA (Acrylate) Mounting/Connection Surface, Indoor Screwless terminal block

Light output 1



| 1 | Χ | LI | ΞI |) |
|---|-----|----|----|----|
| Ν | loi | m | in | 12 |

| Nominal lamp power | |
|--------------------|-----|
| Lamp flux | 23 |
| Luminous efficacy | 129 |
| CCT | 40 |
| CRI | |

| 18 W | LOR |
|--------|-------------|
| 330 lm | ULOR |
| lm/W | Total flux |
| 1000 K | Total power |
| 80 | |

| LOR | 100% |
|-------------|---------|
| ULOR | 7% |
| Total flux | 2330 lm |
| Total power | 18 W |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.17 in Width: 5.93 in Height: 2.09 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 18 W Appliance Class: I

Protection

IP: 44 IK: 05