Product data sheet

ALPHABET SPECTRA RECESSED LUMINAIRE, DOWNLIGHT AS1102004-30-40 + 83819R10-WT_16W

SCHMITZ | WILA








alphabet spectra LED 4000 K Recessed Luminaire, Light distribution direct Downlight Reflector white coated Product: AS1102004-30-40 Operating technology: independent driver required Lite Optic: 83819R10-WT Lite Optic Aluminium reflector, coated white Reflector with safety strap for easy installation Half-peak divergence α = 60° Light Technique CRI 98 (typ.), with R9≥90, R15≥95 highest colour consistency with 1x2 SDCM (initial), max. 3 SDCM covered by 5 years warranty constant colour temperature 4000 K lifetime 50.000 h (L80/B10); 50.000 h (L70/B0) covered by 5 years warranty Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling ring colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 16 W Colour Rendering Index: 98 Colour Temperature: 4000 K Luminaire Luminous Flux: 1040 Llm System Efficiency: 58 Llm/W Half-peak Divergence α: 60° Number Luminaires LZ: 0.13 Connector: Screw Connector, 3 x 1.5 mm2 Reflector Size: R10 Diameter D: 127 mm Cutout CO: 120 mm Installation Depth RD: 110 mm Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AS1102004-30-40+83819R10-WT_16W

Light output 1



1 x General service incandes	cent lamp
Nominal lamp power	18 V

Lamp flux 1040 lm
Luminous efficacy 58 lm/W
CCT 4000 K
CRI 98

LOR 100%
Total flux 1040 lm
Total power 18 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.33 in Diameter: 5.00 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 18 W Appliance Class: II

Protection

IP: 20