


Product data sheet

LOUI 50
925323.003.1.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Eckmodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Nur optional: Lichtbandsystem vorbereitet für Seilabhängung! Colour: deep black, matt (RAL;9005) Length: 593;mm Width: 593;mm Height: 75;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 28;W Rated luminous flux: 2950;lm Luminous efficiency: 105;lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP;20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	2950 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.35 in
Width: 23.35 in
Height: 2.95 in

Adjustability

Fixed

Electric

System power: 28 W

Protection

IP: 20
IK: 03