


# Product data sheet

OCULUS LINEAR LED 590MM  
830  
BRIGHT SPECIAL LIGHTING




Housing :Extruded aluminium Diffuser :Matt opal cover of extruded PMMA Control Gear :Built-in electronic driver Watt :Max 2x131.2W IP :40 IK :05 • LED replacement with tools

## Light output 1



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 33.8 W   | LOR         | 100%    |
| Lamp flux          | 3528 lm  | ULOR        | 50%     |
| Luminous efficacy  | 114 lm/W | Total flux  | 3528 lm |
| CCT                | 3114 K   | Total power | 31 W    |
| CRI                | 84       |             |         |



|                    |          |             |         |
|--------------------|----------|-------------|---------|
| 1 x LED            |          |             |         |
| Nominal lamp power | 22.7 W   | LOR         | 100%    |
| Lamp flux          | 2352 lm  | ULOR        | 50%     |
| Luminous efficacy  | 104 lm/W | Total flux  | 2352 lm |
| CCT                | 3114 K   | Total power | 22.6 W  |
| CRI                | 84       |             |         |

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 12.99 in  
Width: 24.58 in  
Height: 2.36 in

## Adjustability

Height adjustable

## Electric

System power: 22.6-31 W  
Appliance Class: I

## Protection

IP: 40  
IK: 05