

Product data sheet


GLASSGLASS
D31 P/9
LUCEPLAN



IP
20


La versatilità di un sistema componibile e l'eleganza del pezzo unico. La struttura a maniglia in alluminio pressofuso sostiene con sicurezza una serie di vetri diffusori realizzati secondo le antiche tradizioni della soffiatura. Il cavo elettrico, ingabbiato in una maglia di acciaio, è portante.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	205 W	Socket	E27
Lamp flux	2520 lm	LOR	84%
Luminous efficacy	9 lm/W	ULOR	47%
CCT	2821 K	Total flux	2125 lm
CRI	99	Total power	250 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	140 W	Socket	E27
Lamp flux	2840 lm	LOR	84%
Luminous efficacy	10 lm/W	ULOR	47%
CCT	3000 K	Total flux	2395 lm
CRI	99	Total power	250 W



1 x Halogen low voltage lamp without reflector

Nominal lamp power	105 W	Socket	E27
Lamp flux	1980 lm	LOR	84%
Luminous efficacy	7 lm/W	ULOR	47%
CCT	3000 K	Total flux	1670 lm
CRI	99	Total power	250 W

Mounting mode

Pendant

Electric

System power: 250 W

Shape and measurements

Length: 9.12 in

Width: 8.96 in

Height: 22.12 in

Adjustability

Fixed

Protection

IP: 20