Product data sheet

NADJA III (WALL FITTING BEADED) 9.846.2036.06

LEIPZIGER LEUCHTEN








Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1




1 x High pressure sodium vapour	lamp
Nominal lamp power	50 V

remain amp	00
Lamp flux	3500 lm
Luminous efficacy	44 lm/W
CCT	2000 K
CRI	25

LOR 78% Total flux 2729 lm

Total power 62 W



1 x High pressure sodium vapour lamp

• •			
Nominal lamp power	70 W	LOR	78%
Lamp flux	5600 lm	Total flux	4366 lm
Luminous efficacy	53 lm/W	Total power	83 W
CCT	2000 K		

25

Mounting mode Electric

Wall mounted System power: 62-83 W

CRI

Shape and measurements Protection

Height: 16.54 in IP: 55

Diameter: 16.54 in Designation labels: CE, ENEC, F