


# Product data sheet


SBR460[Q] IP54:HIT/S 400W/E40  
138-9677  
WE-EF



IP  
54

IP54. Marine-grade aluminium alloy body. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens. Anodised aluminium reflector. 40°C ambient temperature rating for versions up to 250 W. Integral HPF control gear in thermally separated compartment. LPF versions are available on request. Optional (factory-installed) LIS lamp ignition sensor activates an integral tungsten halogen lamp following a cold start or a momentary power interruption. Deactivates the lamp once the main H.I.D. lamp reaches 50% of its objective brightness. 25°C ambient temperature rating. Suitable for the lighting of sports halls, indoor swimming pools and ice rinks, greenhouses, warehouses, factories, petrol stations, etc.

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	400 W	Socket	E40
Lamp flux	35000 lm	LOR	77%
Luminous efficacy	59 lm/W	Total flux	27071 lm
CCT	5200 K	Total power	460 W
CRI	95		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 25.98 in  
Width: 17.13 in  
Height: 9.06 in

## Electric

System power: 460 W

## Protection

IP: 54