


Product data sheet

FUJI-ROUND WALL LIGHT
7511-0-3-751-XX
UNILAMP




Description FUJI is a family of shielded bollard. It gives symmetrical light distribution on illuminated surfaces. Fuji is operated with high power COB LED from world renowned manufacturer. It is generally installed in the walkways, parks, commercial areas and open spaces. It provides general lighting in the architectural environment where light pollution has to be controlled. We can supply the bollard at different heights according to customer designs. Anchor unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium reflector. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	G12
Lamp flux	3300 lm	LOR	20%
Luminous efficacy	14 lm/W	ULOR	3%
CCT	4000 K	Total flux	661 lm
CRI	98	Total power	48 W



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	G12
Lamp flux	3300 lm	LOR	20%
Luminous efficacy	14 lm/W	ULOR	3%
CCT	3000 K	Total flux	661 lm
CRI	84	Total power	48 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.09 in

Width: 9.85 in

Height: 14.80 in

Electric

System power: 48 W

Appliance Class: I

Protection

IP: 54

IK: 08

Adjustability

Fixed