


# Product data sheet

MARVIK 5 WALL SURFACE LUMINAIRES  
MV-30042-EW-EW-W40  
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4032 K |
| Nominal lamp power | 11 W    | CRI         | 80     |
| Total flux         | 768 lm  | LOR         | 100%   |
| Luminous efficacy  | 70 lm/W | Total power | 11 W   |

## Light output 2 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4032 K |
| Nominal lamp power | 11 W    | CRI         | 80     |
| Total flux         | 768 lm  | LOR         | 100%   |
| Luminous efficacy  | 70 lm/W | Total power | 11 W   |

## Mounting mode

Wall mounted

## Shape and measurements

Height: 7.87 in  
Diameter: 6.97 in  
Weight: 2.6 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 22 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C