

# Product data sheet


DEFINE LED SUSPENDED LUMINAIRE  
S122RDIP-S865D330U830-4F0-1E-UDD-A4  
COOPER LIGHTING



IP  
47

Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 43.5 W  | CRI         | 80     |
| Total flux         | 4317 lm | LOR         | 100%   |
| Luminous efficacy  | 99 lm/W | ULOR        | 28%    |
|                    |         | Total power | 43.5 W |

## Mounting mode

Pendant

## Shape and measurements

Length: 48.00 in

Width: 2.00 in

Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 43.5 W

## Protection

IP: 47