


Product data sheet

SCOUT 204.930.50.2 50°
SCOUT 204.930.50.2
LTS LICHT & LEUCHTEN



flexible track-mounted spotlight in separated design with cylindrical light-head, light-head rotates through 355° and pivots through 90° via integrated articulated arm, outstanding ease of maintenance, no UV and thermal emissions, light-head made from die-cast aluminium, innovative thermal management with design-integrated passive cooling, high performance specular aluminium reflector with precise symmetrical beam characteristic for high luminous efficiency and glare-free lighting, ballast housing made from aluminium, clear and reflection-free EnergyVision safety glass, 3-phase track adapter, ballast (LED converter) integrated Lamp: LED Spot | 930 | CRI 90 | 3000 K Lifetime: L90 B50 50.000 h / L80 B50 100.000 h / L80 B20 50.000 h EPREL light sources: 860292 beam angle: 50° beam range: 50° Protection class: I Type of protection: IP20 Standards: CE,RoHS Diameter of light head: 96 mm Dimensions (LxBxH): 212 x 96 x 164 mm Weight: 1.155 kg Colour: silver (article no. 660541), black (article no. 660542), white (article no. 660543) Accessories: ST-A 10/9000A-1-ST surface-mounted track ONETrack Advance with data bus (length: 1000 mm) ST-A 20/9000A-2-ST surface-mounted track ONETrack Advance with data bus (length: 2000 mm) ST-A 30/9000A-3-ST surface-mounted track ONETrack Advance with data bus (length: 3000 mm) ST-A 40/9000A-4-ST surface-mounted track ONETrack Advance with data bus (length: 4000 mm) ST-A MONO/9000-BPU-D 3-phase surface-mounted monopoint with bus option ST-E 10/9000-1-R recessed track ONETrack with data bus (length: 1000 mm) ST-E 20/9000-2-R recessed track ONETrack with data bus (length: 2000 mm) ST-E 30/9000-3-R recessed track ONETrack with data bus (length: 3000 mm) ST-E 40/9000-4-R recessed track ONETrack with data bus (length: 4000 mm) ST-E MONO/9000-BPU-D 3-phase recessed monopoint with bus option ZBK 13 anti-glare flaps ZBW 87 honeycomb louvre Manufacture: LTS Type: SCOUT 204.930.50.2

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	37.5 W	CRI	90
Total flux	3970 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	37.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.46 in

Diameter: 3.78 in

Electric

System power: 37.5 W

Appliance Class: I

Protection

IP: 20