


Product data sheet

AREA 66 GREY 5930LM 4000K RA>80 ON/OFF
7021981200022
SG ARMATUREN



IP66 luminaire for mounting on ceiling. Made of UV-stabilised polycarbonate. The slim design, unique one-hand closing mechanism at both ends, through wiring and option of looping ensures very quick and simple installation. Can be used in cold rooms with temperatures down to -25°C. 5-pole (On/Off) or 7-pole (DALI) terminal block with 5 x 2,5 mm². Light distribution Direct Light technic LED (not exchangeable) 46W 4000K Ra>80 SDCM 3 L80/B50 >100,000 hrs L90/B50 >50,000 hrs Control/Dimming On/Off Protection Class I IP66 IK10 Fire protection class: 850°C - 30s Energy and approvals CE Materials and finish Housing: UV-stabilized polycarbonate Colour: Grey Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 8, B16: 13, C10: 13, C16: 22

Light output 1



1 x LED			
Nominal lamp power	46 W	LOR	100%
Lamp flux	5930 lm	ULOR	5%
Luminous efficacy	129 lm/W	Total flux	5931 lm
CCT	4000 K	Total power	46 W
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 57.93 in
Width: 3.63 in
Height: 2.76 in

Adjustability

Fixed

Electric

System power: 46 W
Appliance Class: I

Protection

IP: 66
IK: 10