


Product data sheet

ALU-KREIS
251042.003
RZB



Series: Alu-Kreis Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: jet black (RAL 9005) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 230, H 110 Lamp: LED Life time: 33000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 800lm System power: 18W Beam Angle: 149° Unified Glare Ratio: 19,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18 W	CRI	80
Total flux	800 lm	LOR	100%
Luminous efficacy	44 lm/W	ULOR	29%
		Total power	18 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.33 in
Diameter: 9.06 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 18 W

Protection

IP: 43
IK: 02