

Product data sheet

LAVANO UNO
451198.000
RZB




IP
40

IK
02

Series: Lavano UNO Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base and dead ends anodised stainless steel, brushed, diffuser plastic, opal, allows for brilliant glittering light along the lines of the ellipse. Available Colours: white aluminium (RAL 9006)
Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 580, B 40, H 83 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1250lm System power: 13W Beam Angle: 152°/114° Number of fittings B10A: 10 Number of fittings B16A: 17 Number of fittings C10A: 16 Number of fittings C16A: 26 Inrush current: 49A Unified Glare Ratio: 24,6 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1250 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	23%
		Total power	13 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.27 in
Width: 22.83 in
Height: 1.57 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 13 W

Protection

IP: 40
IK: 02