


Product data sheet

PURE 3 DOWNLIGHT
09.1803/HIT-CRI/35W/70W/150W/13°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

Light output 1




1 x Metal halide lamp

Nominal lamp power	35 W	Socket	G12
Lamp flux	3400 lm	LOR	66%
Luminous efficacy	64 lm/W	Total flux	2240 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	150 W	Socket	G12
Lamp flux	14000 lm	LOR	66%
Luminous efficacy	61 lm/W	Total flux	9224 lm
CCT	3000 K	Total power	150 W
CRI	89		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	66%
Luminous efficacy	62 lm/W	Total flux	4349 lm
CCT	3000 K	Total power	70 W
CRI	83		

Mounting mode

Ceiling recessed

Electric

System power: 35-150 W
Appliance Class: I

Shape and measurements

Length: 5.91 in

Width: 5.91 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Protection

IP: 20