

# Product data sheet

O81-110 LED 600 840 MB  
GLAMOX




IP  
66

IK  
09

Light source LED 600 - 6000 lumen out Colour temperature 3000/4000 K CRI Ra 80, MacAdams 3 Driver Fixed output (HF). Body material & colour Housing in extruded and die-cast aluminium. Double layer polyester powder coated paint finish in colour aluminium grey (RAL 9006). Tempered glass diffuser. Silicone gasket. Stainless steel screws. Mounting For installation directly on wall, ceiling or solid ground. Connection O81-110: 1 x membrans gland on backside of the luminaire and 3 pole 2,5 mm<sup>2</sup> screw terminal block. O81-220: 2 x membrane glands on backside of the luminaire and 3 pole 2,5 mm<sup>2</sup> push-in terminal block. Outdoor use requires suitable flexible cables assuring the water tightness of the membrane gland. Optics Medium beam (MB). Narrow beam (NB). Protection against surges O81-110: Up to 2kV O81-220: Up to 4kV

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 13 W    | CRI         | 80     |
| Total flux         | 547 lm  | LOR         | 100%   |
| Luminous efficacy  | 42 lm/W | Total power | 13 W   |

## Mounting mode

Ceiling mounted

## Electric

System power: 13 W

## Shape and measurements

Height: 5.31 in  
Diameter: 4.33 in

## Protection

IP: 66  
IK: 09

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: Silver gray