

# Product data sheet


LSR2B, LSSQ2B LED 2" ROUND AND SQUARE CYLINDERS  
LSRWM2B10SP159024D010 2LBDL H  
COOPER LIGHTING



IP  
47

Distributions: 15°, 25°, 40° and 55°, Mounting: ceiling, wall or stem, Extruded aluminum housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 500, 1,000 1,500 and 2,000, Colors: Matte Black, Matte White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

## Light output 1 (integrated)



Lamp type	LED	CCT	2400 K
Nominal lamp power	10.3 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	38 lm/W	Total power	10.3 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.39 in  
Diameter: 2.00 in

## Adjustability

Fixed

## Electric

System power: 10.3 W

## Protection

IP: 47