

Product data sheet


SCAPHA
311989.004
RZB



IP
20

Series: Scapha Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: aluminium, powder-coated. Canopy and glass fixture steel powder-coated. Handmade concave glass, matt finish on the outside, painted white on the inside. Lamp (LED) included. Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 714, B 134, H 100 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Luminaire flux LED: 2350lm System power: 35W Beam Angle: 162°/113° Number of fittings B10A: 13 Number of fittings B16A: 21 Number of fittings C10A: 22 Number of fittings C16A: 35 Inrush current: 21A Unified Glare Ratio: 24,8 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	2350 lm	LOR	100%
Luminous efficacy	67 lm/W	ULOR	11%
		Total power	35 W

Mounting mode

Wall mounted

Electric

System power: 35 W

Shape and measurements

Length: 5.28 in
Width: 28.11 in
Height: 3.94 in

Protection

IP: 20

Adjustability

Fixed