


Product data sheet

QUANTUM 1 CLUSTER COLUMN PROJECTORS
QA-21011-M-W40
LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° > 61,000 - Life time L80B10 Ta 50° > 61,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector or PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	41.7 W	CRI	80
Total flux	3624 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	41.7 W

Light output 2 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	41.7 W	CRI	80
Total flux	3624 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	41.7 W

Light output 3 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	41.7 W	CRI	80
Total flux	3624 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	41.7 W

Light output 4 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	41.7 W	CRI	80
Total flux	3624 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	41.7 W

Light output 5 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	41.7 W	CRI	80
Total flux	3624 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	41.7 W

Light output 6 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	41.7 W	CRI	80
Total flux	3624 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	41.7 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Height: 157.48 in
Diameter: 31.77 in
Weight: 47.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 250.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C