

Product data sheet

QUANTUM 2 STREET AND AREA LIGHTING LUMINAIRES


QA-21024-T4-W40

LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 60,900 - Life time L80B10 Ta 50° > 72,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	81.5 W	CRI	80
Total flux	8859 lm	LOR	100%
Luminous efficacy	109 lm/W	Total power	81.5 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 5.67 in
Diameter: 11.81 in
Weight: 10.8 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 81.5 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C