


Product data sheet

RAX 200 WHITE 31W 4000K RA>80 DALI
8246079651
SG ARMATUREN



Flush-mounted LED downlight. Made of fire-resistant polycarbonate. SDCM 2. L90/B10>100,000 hours, Supplied with 3000K/4000K LED. Complete with driver and quick connection between driver and downlight for super quick and easy mounting. Can be mounted to ceiling panels with a thickness of 1–50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector. Light distribution: Direct Light technic LED 31W 4000K Ra>80 SDCM 2 L90/B10 >100,000 hrs at Ta=25°C Control/Dimming DALI Push Dim Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Flame retardant polycarbonate Colour: White Optics: Aluminium Mounting/Connection Recessed (downlight), Indoor Max. luminaires per circuit breaker: B10: 33, B16: 55, C10: 53, C16: 88

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31 W	CRI	80
Total flux	3610 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	31 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 8.78 in
Width: 8.78 in
Height: 4.22 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 31 W
Appliance Class: I

Protection

IP: 20