

Product data sheet


COMPASS SPOT
03.3323/HIT-CRI/70W/25°
FLOS



IP
20


Range of indoor spotlights for accent and general lighting for three-phase track and wall/ceiling installation. Die-cast aluminium alloy, powder-coated optics compartment, diameter 118 mm, composed of an aluminium dissipating element placed above the lamp support, a black thermoplastic screen support ring and 4 mm tempered glass cover. Integrated auxiliary power units for the lamps inside a die-cast aluminium alloy container with powder-coated finish.

Light output 1



1 x Metal halide lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W | Socket | G12 |
| Lamp flux | 6600 lm | LOR | 67% |
| Luminous efficacy | 62 lm/W | Total flux | 4399 lm |
| CCT | 4200 K | Total power | 71 W |
| CRI | 94 | | |



1 x Metal halide lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W | Socket | G12 |
| Lamp flux | 6600 lm | LOR | 67% |
| Luminous efficacy | 62 lm/W | Total flux | 4399 lm |
| CCT | 3000 K | Total power | 71 W |
| CRI | 83 | | |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in

Width: 4.72 in

Height: 5.83 in

Adjustability

Free

Electric

System power: 71 W

Protection

IP: 20