Product data sheet

FLAT POLYMERO 311556.002.7

RZB












Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Colour: white Diameter: 620 mm Height: 160 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28 W Rated luminous flux: 3100 lm Luminous efficiency: 111 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	3100 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	11%
		Total power	28 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.30 in Diameter: 24.41 in

Adjustability

Fixed

Design

Material impression: Matt

Electric

System power: 28 W

Ballast: ECG

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 40

IK: 03

Designation labels: CE, ENEC, F

Other operating numbers

Ambient temperature range: -4...95°F