

Product data sheet

FLAT BASIC
211400.002.19
RZB




IP
43

IK
02

Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. Functional parameters of a master luminaire (ceiling height of approx. 2.8m): HF detector 24GHz with integrated corridor function. Coverage: approx. 130° radial. Easy adjustment of functions via associated push button switches. Sensitivity/Range: 0.5-5m radial, adjustable from 10-100%. Time control 1second to 15minutes in 8different levels. Daylight detection with 5brightness levels and learning mode. Up to 9slave luminaires can be operated with one master luminaire (max. up to 150W / 230W). Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: pure white (RAL9010) Diameter: 420mm Height: 124mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 83 System power: 12W Rated luminous flux: 1200lm Luminous efficiency: 100lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP43

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	16%
		Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.88 in
Diameter: 16.54 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 43
IK: 02