


Product data sheet

ZET5 - OPTIC ADJUSTABLE CLEAR
9013-A-2-530-91
UNILAMP



ZET a walk-over in ground uplighter is operated with multiple high power LED or AC COB for trouble free installation. The anti-condensation kit is factory fitted and equipped within the luminaire to ensure humidity cannot penetrate into the luminaire. ZET is commonly used to highlight small architectural works, wall structures, low ceilings, and columns. The glare-shield honey comb and softening lens are available as accessories. An IP68 connection kit for water tight connection is also available. For all luminaire of this nature the installation process has to be done according to the product manual. • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1, IEC 60598-2-13 and VDE regulations. • Marine grade 316 stainless steel front cover. • LM6 die-cast aluminium body. • GFR polymer recess housing. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module. • High efficiency reflector for AC version. • Molded Lens from renowned manufacturer. • M16 cable gland. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual. • For ground recess application, the water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light output 1



1 x LED			
Nominal lamp power	8.1 W	LOR	90%
Lamp flux	1030 lm	ULOR	89%
Luminous efficacy	127 lm/W	Total flux	924 lm
CCT	4000 K	Total power	8.1 W
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 5.08 in
Width: 5.08 in
Height: 6.85 in

Adjustability

Fixed

Electric

System power: 8.1 W
Appliance Class: III

Protection

IP: 67
IK: 10