# Product data sheet


DEFINE LED SUSPENDED LUMINAIRE S122DIP-S865D530U940-4F0-1E-UDD-D1 COOPER LIGHTING



COOPER Lighting Solutions

Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

## Light output 1 (integrated)



LED	CCT	4000 K
48.8 W	CRI	90
4802 lm	LOR	100%
98 lm/W	ULOR	42%
	Total power	48.8 W
	48.8 W 4802 lm	48.8 W CRI 4802 lm LOR 98 lm/W ULOR

## Mounting mode

Pendant

# Shape and measurements

Length: 48.00 in Width: 2.00 in Height: 1.00 in

## Adjustability

Fixed

### Electric

System power: 48.8 W

### Protection

IP: 47