



Product data sheet

LADOR 10 SURFACE EXTERIOR DOWNLIGHTS
LD-80011-W-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11.4 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	72 lm/W	Total power	11.4 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 3.23 in
Width: 3.23 in
Height: 4.65 in
Weight: 1.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 11.4 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C