



Product data sheet

GANDALF 24 STREET AND AREA LIGHTING LUMINAIRES
GA-90241-T3-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10 kV

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 37.6 W | CRI | 80 |
| Total flux | 4848 lm | LOR | 100% |
| Luminous efficacy | 129 lm/W | Total power | 37.6 W |

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 16.18 in
Width: 12.60 in
Height: 4.72 in
Weight: 9.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 37.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C