


# Product data sheet

FLEX STRIP IP53 400 HE+ MONO - SWW  
L644926HL  
PROLED (MBN GMBH)



The PROLED FLEX STRIPS are perfect for indirect lighting, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities. - High efficiency - High flexibility – adaptable to round shapes. - Installation with 3M adhesive tape on the strip's backside (self adhesive). - IP53 only if glued correctly and if the sides are sealed with glue. - dimmable and controllable via DMX 512, DALI, KNX, 1-10 V, CASAMBI, RF by MULTI power supplies/controller

## Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	14.4 W	CRI	90
Total flux	1500 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	14.4 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 39.37 in

Width: 0.39 in

Height: 0.12 in

## Adjustability

Fixed

## Electric

System power: 14.4 W

Controller: Dimmable 1..10V, DMX, DALI

Appliance Class: III

## Protection

IP: 53

## Other operating numbers

Ambient temperature range: 14...113°F