# Product data sheet

MAR 10 STREET AND AREA LIGHTING LUMINAIRES MA-97091-EW-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10kV

## Light output 1 (integrated)



Lamp type	LED
Nominal lamp power	37.4 W
Total flux	4916 lm
Luminous efficacy	131 lm/W

LED	CCT	4032 K
37.4 W	CRI	80
4916 lm	LOR	100%
131 lm/W	Total power	37.4 W

### Mounting mode

Wall mounted, Pole top mounted

### Shape and measurements

Height: 10.24 in Diameter: 17.24 in Weight: 15.8 kg

## Adjustability

Fixed

### Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

### Electric

System power: 37.4 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Protection

IP: 55 IK: 07

Surface temperature: 40°C