

Product data sheet

ALU-KREIS
25201.003
RZB




IP
43

IK
02

Series: Alu-Kreis Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated.
Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: jet black (RAL 9005) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 230, H 110 Lamp: LED Colour Temperature: 6300K
Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule)
Luminaire flux LED: 410lm System power: 12W Beam Angle: 142° Unified Glare Ratio: 17,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	6300 K
Nominal lamp power	12 W	CRI	60
Total flux	410 lm	LOR	100%
Luminous efficacy	34 lm/W	ULOR	25%
		Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.33 in
Diameter: 9.06 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 12 W

Protection

IP: 43
IK: 02