


# Product data sheet

FLAT POLYMERO  
672133.002.7.07  
RZB




IP  
40

IK  
03

Item Number: 672133.002.7.07 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Self-contained system, with integrated self-test and response via Dali bus, exclusively to the RZB 985405 monitoring system. Additional status indicator placed on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, , H 120mm Lamp: LED + LED 1.5 W Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 8h Emergency Lighting System: DALI-Sibe Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 22W Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	2050 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	10%
		Total power	19 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 4.72 in  
Diameter: 18.11 in

## Adjustability

Fixed

## Electric

System power: 19 W

## Protection

IP: 40  
IK: 03