


# Product data sheet

POLYMERO CLASSIC  
311640.002.8  
RZB




IP  
40

IK  
10

Series: Polymero Classic Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 90 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1400lm System power: 14W Beam Angle: 122° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 19,9 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	80
Total flux	1400 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	19%
		Total power	14 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 3.54 in  
Diameter: 11.81 in

## Adjustability

Fixed

## Electric

System power: 14 W

## Protection

IP: 40  
IK: 10