# Product data sheet

JET 40 SURFACE EXTERIOR DOWNLIGHTS
JE-80041-M-W40
LIGMAN

IP 65   IK 08

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

---

Light output 1 (integrated)

Lamp type	LED	CCT	4032 K
Nominal lamp power	15 W	CRI	80
Total flux	1101 lm	LOR	100%
Luminous efficacy	73 lm/W	Total power	15 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 4.02 in
Width: 4.02 in
Height: 9.13 in
Weight: 2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 15 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C