

# Product data sheet

NADJA VII (1-ARMED BEADED)  
9.876.3066.86  
LEIPZIGER LEUCHTEN




Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711  
Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	78%
Lamp flux	6800 lm	Total flux	5302 lm
Luminous efficacy	39 lm/W	Total power	137 W
CCT	3400 K		
CRI	54		



### 1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	78%
Lamp flux	4000 lm	Total flux	3119 lm
Luminous efficacy	35 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

## Mounting mode

Pole top mounted, Ceiling mounted

## Shape and measurements

Height: 16.54 in  
Diameter: 16.54 in

## Design

Material impression: Matt  
Color of housing: White

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 89-137 W  
Ballast: ECG  
Controller: DALI

## Protection

IP: 55  
Designation labels: CE, ENEC

#### Other operating numbers

Ambient temperature range: 32...95°F