

Product data sheet

FLAT POLYMERO KREIS
311979.002.3.76
RZB




IP
40

IK
03

Series: FLAT POLYMERO KREIS Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 35 mm. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Homogeneous and smooth light distribution. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. TouchDim sensor capable. Light and/or presence sensors can be integrated. Colour: white Diameter: 460 mm Height: 93 mm Suspension length: 200-1300 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 83 System power: 19 W Rated luminous flux: 2000 lm Luminous efficiency: 105 lm/W Control gear: AC power, DALI dimmable Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	2000 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	14%
		Total power	19 W

Mounting mode

Pendant

Shape and measurements

Height: 3.66 in
Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 19 W

Protection

IP: 40
IK: 03