


Product data sheet

LADOR 2 FLOODLIGHTS,PROJECTORS
LD-50011-M-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° C 135,000, 200,000 - Life time L80B10 Ta 50° C 310,000, > 490,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request for LD-50021, LD-50031 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11.2 W	CRI	80
Total flux	792 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	11.2 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 3.74 in
Width: 3.23 in
Height: 4.92 in
Weight: 1 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 11.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C