

Product data sheet

FLAT POLYMERO KREIS
311949.002.2.19
RZB




IP
40

IK
10

Series: FLAT POLYMERO KREIS Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Master luminaire. With integrated HF movement sensor. HF detector 24 GHz with integrated corridor function. Coverage: approx. 130° radial. Easy adjustment of functions via 3 associated push button switches. Sensitivity/Range: 0.5-5 m radial, adjustable from 10-100%. Time control 1 second to 15 minutes in 8 different levels. Daylight detection with 5 brightness levels and learning mode. Up to 9 slave luminaires can be operated with one master luminaire (max. up to 150 W / 230 W). Suitable for outdoor use to a limited extent only, as it is sensitive to all movements Colour: white Diameter D: 300 mm Height H: 80 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI):83 System power 1: 12 W Rated luminous flux 1: 1200 lm Luminous efficiency: 100 lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	18%
		Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.15 in
Diameter: 11.81 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 40
IK: 10