Product data sheet

RADIIS 210 Ø280 WALLWASHER 106X66, LED 36W/3000K 5747829497

LOUIS POULSEN








Radiis 210 Concept: The fixture emits even, channelled light. Three types of light systems – zoom, lens and wall washer – together with direction adjustment options and colour and light filters, make it possible to illuminate buildings, vegetation, signs, etc. in an effective and interesting way, while promoting a sense of security. Finish: Glass, stainless steel. Material: Housing: Injection moulded anodised aluminium. Top ring: Brushed stainless steel, 316L. Glass: Extra clear, hardened glass. Driver box: Synthetic. Installation sleeve: Synthetic. Mounting: An installation sleeve must be used (ordered separately). The IP68 driver box/connection box is pre-mounted with sealed wiring and IP68 connectors. The connecting cable terminates with an IP68 connector (supplied) for cable type H07RN-F Ø7-12mm (2x2.5mm2). Looping: Yes. Certified to withstand load of up to 2,000 kg. Weight: Max. 6kg. Class: Ingress protection IP66, IP67, IP68, IP69K. IK10. Electric shock protection II wo. ground.

Light output 1



1 x LED	
Nominal lamp power	
Lamp flux	
Luminous efficacy	
CCT	
CRI	

36 W	LOR	
3520 lm	ULOR	
50 lm/W	Total flux	
3000 K	Total power	
80		

51%
51%
1793 lm
36 W

Mounting mode

Floor recessed

Shape and measurements

Height: 0.39 in Diameter: 11.02 in

Adjustability

Tiltable

Electric

System power: 36 W Appliance Class: II

Protection

IP: 67