

# Product data sheet

AVIATO  
741761.003  
RZB




IP  
20

IK  
02

Series: Aviato Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing die-cast aluminium powder-coated, can be rotated 356° horizontally and swivelled 180° vertically, passive cooling, without reflector aluminium faceted, order reflector assembly separately, replaceable LED module, LED included in delivery, with multi-adapter for 3-phase tracks 230V, ceiling mounting. Available Colours: deep black, matt (RAL 9005) Type of Installation: Track on ceiling Dimensions: L 208, B 106, H 237 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3100K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1950lm System power: 28W Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	28 W	CRI	90
Total flux	1950 lm	LOR	100%
Luminous efficacy	70 lm/W	Total power	28 W

## Mounting mode

Ceiling mounted

## Electric

System power: 28 W

## Shape and measurements

Length: 4.17 in

Width: 8.19 in

Height: 9.33 in

## Protection

IP: 20

IK: 02

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: Black