Product data sheet

NADJA III (2-ARMED) 9.877.2032.05

LEIPZIGER LEUCHTEN








Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium,burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure sodium vapour lamp	
Nominal lamp power	70 W
Lamp flux	5600 lm
Luminous efficacy	53 lm/W
CCT	2000 K
CRI	25

LOR 78%
Total flux 4379 lm
Total power 83 W

Light output 2



1 x High pressure sodium vapour lamp	
Nominal lamp power	70 W
Lamp flux	5600 lm
Luminous efficacy	53 lm/W
CCT	2000 K

CRI

LOR 78%
Total flux 4379 lm
Total power 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 16.54 in Diameter: 16.54 in Electric

System power: 166 W

25

Protection

IP: 55