


Product data sheet

VEKTER 13 STREET AND AREA LIGHTING LUMINAIRES
VK-20012-T3-W40
LIGMAN




High-power LED · Colour stability · Mac Adam < 3 · Life time : 50000 h · Colour temperature : 3000K and 4000K Flexible tapered column-mounted floodlighting and area luminaires. Sleek, angular, technical and powerful professional lighting solutions with a graceful twist.

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.7 W	CRI	80
Total flux	3101 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	27.7 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.7 W	CRI	80
Total flux	3101 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	27.7 W

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 27.40 in
Width: 10.24 in
Height: 13.39 in
Weight: 56.2 kg

Adjustability

Free

Glare protection

Glare protection: UGR < 19

Electric

System power: 55.4 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C