Product data sheet

SMART CAKE 115 IP54 DIFFUSE LED GE 2700K WHITE STRUC 12743009

MODULAR









Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. What you get is a LED module with a different finish. The light flows over the edges of the Smart Cake like its bigger sister.

Light output 1




| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 11 V |
| Lamp flux | 1065 ln |
| Luminous efficacy | 68 lm/V |
| CCT | 2700 H |
| CRI | 90 |

| LOR | | 70 |)% |
|-----------|------|-------|----|
| Total flu | JX | 749 l | n |
| Total po | ower | 11 | V |
| | | | |



| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 23.6 W |
| Lamp flux | 1943 lm |
| Luminous efficacy | 58 lm/W |
| CCT | 2700 k |
| CRI | 90 |

| LOR | 70% |
|-------------|---------|
| Total flux | 1366 lm |
| Total power | 23.6 W |
| | |



| 1 x LED | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 16.25 W | LOR | 70% |
| Lamp flux | 1461 lm | Total flux | 1027 lm |
| Luminous efficacy | 63 lm/W | Total power | 16.25 W |
| CCT | 2700 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.20 in Diameter: 4.53 in

Adjustability

Fixed

Electric

System power: 11-23.6 W Appliance Class: II

Protection

IP: 54