


Product data sheet

SMART CAKE 160 IP55 LED GE 4000K MEDIUM WHITE STRUC
13004509
MODULAR




Soft light Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


Light output 1




| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 36.3 W | LOR | 84% |
| Lamp flux | 4427 lm | Total flux | 3727 lm |
| Luminous efficacy | 103 lm/W | Total power | 36.3 W |
| CCT | 4000 K | | |
| CRI | 90 | | |




| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 30.8 W | LOR | 84% |
| Lamp flux | 3828 lm | Total flux | 3223 lm |
| Luminous efficacy | 105 lm/W | Total power | 30.8 W |
| CCT | 4000 K | | |
| CRI | 90 | | |




| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 23.5 W | LOR | 84% |
| Lamp flux | 3084 lm | Total flux | 2596 lm |
| Luminous efficacy | 110 lm/W | Total power | 23.5 W |
| CCT | 4000 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 16 W | LOR | 84% |
| Lamp flux | 2265 lm | Total flux | 1907 lm |
| Luminous efficacy | 119 lm/W | Total power | 16 W |
| CCT | 4000 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 49.7 W | LOR | 84% |
| Lamp flux | 5725 lm | Total flux | 4820 lm |
| Luminous efficacy | 97 lm/W | Total power | 49.7 W |
| CCT | 4000 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 42 W | LOR | 84% |
| Lamp flux | 4972 lm | Total flux | 4186 lm |
| Luminous efficacy | 100 lm/W | Total power | 42 W |
| CCT | 4000 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 4.76 in

Weight: 0.98 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W

Appliance Class: II

Protection

IP: 55