Product data sheet

LER4B/LESQ4B LED 4" ROUND AND SQUARE CYLINDERS LE_4B10D010 EC4B10209024 4LBM1GPH


COOPER LIGHTING



Distributions: narrow (30°), medium (50°) and wide (75°) beams, Mounting: ceiling, wall, stem, aircraft cable; Down or up/down styles, Extruded aluminum housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W[™] option from 3000K to 1850K, Lumens: 1,000-4,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

IP 47

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.9 W	CRI	100
Total flux	486 lm	LOR	100%
Luminous efficacy	49 lm/W	Total power	9.9 W

Mounting mode	Electric	
Ceiling recessed	System power: 9.9 W	
Shape and measurements	Protection	
Length: 3.94 in	IP: 47	
Width: 3.94 in		
Height: 3.94 in		

Adjustability

Fixed