


Product data sheet

MAXI TUBE-RECESS DOWN LIGHT/CLEAR GLASS
7304-5-5-887-XX
UNILAMP



TUBE a family of cylindrical shaped wall light, ceiling light and Area light. The body components are made from extruded and LM6 aluminium which make them highly corrosion resistant to any extreme environment. TUBE is protected from the ingress of dust and water and are used in both outdoor and indoor environments. Fitted with COB LED in three color temperature from 2700K, 3000K or 4000K with high CRI. HID light source and retrofit solution for E27 Led lamps are also available. TUBE can solve many lighting tasks in modern architectural surrounds and are generally used in illuminating columns and facades. The pole lights give a great level of downward light with symmetric wide beam, asymmetric forward throw or side throw light distributions.

Light output 1



1 x LED			
Nominal lamp power	23 W	LOR	92%
Lamp flux	3300 lm	Total flux	3023 lm
Luminous efficacy	143 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 9.25 in

Width: 9.25 in

Height: 11.44 in

Adjustability

Fixed

Electric

System power: 27 W

Controller: DALI

Appliance Class: I

Protection

IP: 65

IK: 06