

Product data sheet

FLAT POLYMERO KREIS
311656.002.78
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 98 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, 1-10V Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3450lm System power: 35W Beam Angle: 123° Unified Glare Ratio: 20,0 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3450 lm	LOR	100%
Luminous efficacy	99 lm/W	ULOR	15%
		Total power	35 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.86 in
Diameter: 20.28 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 40
IK: 03